

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/07/2018 Revision date: 04/15/2015

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Enviro-Chem Shower Stall Cleaner

Product code : ECSHOWER12Q, ECSHOWER1, ECSHOWER5, ECSHOWER55

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet

cleaners, metal cleaners)

1.3. Supplier

Enviro-Brands™
P.O. Box 365

Ridgefield, CT 068

Ridgefield, CT 06877 (844) 368-2763

1.4. Emergency telephone number

Emergency number : (800) 255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

Skin corrosion/irritation Category 1A H314 Causes severe skin burns and eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P260 - Do not breathe dust/mist/spray

P264 - Wash hands and forearms thoroughly after handling P270 - Do not eat, drink or smoke when using this product P280 - Wear protective gloves/eye protection/face protection

P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor

P321 - Specific treatment (see First aid measures on this label)

P330 - Rinse mouth

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

09/04/2019 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Potassium Hydroxide, 45%= <conc<50%, aqueous="" solutions<="" td=""><td>(CAS-No.) 1310-58-3</td><td>10 - 20</td><td>Acute Tox. 3 (Oral), H301 Skin Corr. 1, H314</td></conc<50%,>	(CAS-No.) 1310-58-3	10 - 20	Acute Tox. 3 (Oral), H301 Skin Corr. 1, H314
butyl glycolether	(CAS-No.) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
tetrasodium ethylene diamine tetracetate	(CAS-No.) 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

inimediately call a poison center of doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel

unwell. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met. Harmful if swallowed.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

09/04/2019 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures

Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces,

sparks, open flame and other ignition sources. No smoking. Keep container closed when not in

use.

Incompatible products
Incompatible materials

: Strong bases. Strong acids.

: Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Enviro-Chem Shower Stall Cleaner			
No additional information available			
Potassium Hydroxide, 45%= <conc<50%, aqueous="" s<="" td=""><td colspan="3">Potassium Hydroxide, 45%=<conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,></td></conc<50%,>	Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>		
USA - ACGIH - Occupational Exposure Limits			
Local name	Potassium hydroxide		
Remark (ACGIH)	URT, eye, & skin irr		
butyl glycolether (111-76-2)			
USA - ACGIH - Occupational Exposure Limits			
Local name 2-Butoxyethanol (EGBE)			
ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)		
Remark (ACGIH)	Eye & URT irr		
USA - OSHA - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol		
OSHA PEL (TWA) (mg/m³)	240 mg/m³		
OSHA PEL (TWA) (ppm)	50 ppm		
tetrasodium ethylene diamine tetracetate (64-02-8)			
No additional information available			

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

09/04/2019 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : light brown
Odor : mild

Odor threshold : No data available

pH : 14

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Non flammable. Vapor pressure : No data available Relative vapor density at 20 °C : Same as water

Relative density : 1.03

Solubility : Soluble in water. : No data available Log Pow Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

09/04/2019 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OF OTLONE			
SECTION 1	11. LOVICOL	odical in	tormation
OLC HON	II. IUNICUI	ogical III	ioiiialioii

1	1.1.	. Inf	formation	on t	toxicol	ogical	effects

Acute toxicity (oral) : Harmful if swallowed. Acute toxicity (dermal) Not classified Acute toxicity (inhalation) : Not classified

1767.575 mg/kg body weight ATE US (oral)

Potassium Hydroxide, 45%= <conc<50%, aque<="" th=""><th>ous solutions (1310-58-3)</th></conc<50%,>	ous solutions (1310-58-3)
LD50 oral rat	273 mg/kg (Rat, Oral)
ATE US (oral)	272 mg/kg body woight

butyl glycolether (111-76-2)	
ATE US (oral)	273 mg/kg body weight
LD50 oral rat	273 mg/kg (Rat, Oral)

> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
450 - 486 ppm/4h 450-486,Rat
435 mg/kg body weight
450 ppmV/4h
2.17 mg/l/4h
2.17 mg/l/4h

tetrasodium ethylene diamine tetracetate (64-0)	2-8)
---	------

LD50 oral rat > 2000 mg/kg (Rat, Oral)	
ATE US (oral) 500 mg/kg body weight	

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: 14

Serious eye damage/irritation : Eye damage, category 1, implicit

pH: 14

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

butyl glycolether (111-76-2)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity - single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

: Not classified Aspiration hazard Viscosity, kinematic : No data available

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met. Harmful if swallowed.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. **Toxicity**

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>		
LC50 fish 1	80 mg/l (96 h, Gambusia affinis, Pure substance)	
tetrasodium ethylene diamine tetracetate (64-02-8)		

tetrasodium ethylene diamine tetracetate (64-02-8)	
LC50 fish 1	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 Daphnia 1 625 mg/l (24 h, Daphnia magna, Literature study)	

09/04/2019 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9 9		
tetrasodium ethylene diamine tetracetate (64-02-8)		
LC50 fish 2 396 mg/l		
12.2. Persistence and degradability		
Enviro-Chem Shower Stall Cleaner		
Persistence and degradability	Not established.	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>		
Persistence and degradability	Biodegradability: not applicable.	

<u> </u>	,
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

outyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance
Chemical oxygen demand (COD)	2.2 g O₂/g substance
ThOD	2.305 g O₂/g substance
BOD (% of ThOD)	0.31

tetrasodium ethylene diamine tetracetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O₂/g substance
Chemical oxygen demand (COD)	0.54 - 0.58 g O₂/g substance

12.3. Bioaccumulative potential

Enviro-Chem Shower Stall Cleaner	o-Chem Shower Stall Cleaner	
Bioaccumulative potential	Not established.	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>		
Bioaccumulative potential	Not bioaccumulative.	
butyl glycolether (111-76-2)		
Log Pow	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
tetrasodium ethylene diamine tetracetate (64-02-8)		
Log Pow	-2.6	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

Potassium Hydroxide, 45%= <conc<50%, aque<="" th=""><th colspan="2">tassium Hydroxide, 45%=<conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,></th></conc<50%,>	tassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>	
Ecology - soil	No (test)data on mobility of the components available.	
butyl glycolether (111-76-2)		
Surface tension	0.027 N/m (25 °C)	

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

09/04/2019 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1760 Compounds, cleaning liquid (Contains Potassium Hydroxide), 8, II

UN-No.(DOT) : NA1760

Proper Shipping Name (DOT) : Compounds, cleaning liquid

Contains Potassium Hydroxide

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

: 202

: 242

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Symbols

: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

09/04/2019 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Not subject to reporing requirements of the United States SARA Section 313

CERCLA RQ 1000 lb

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

tetrasodium ethylene diamine tetracetate (64-02-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

EU-Regulations

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/15/2015 Other information : None.

Full text of H-phrases:

H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B

B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

09/04/2019 EN (English US) 8/8